

PRODUCT DATA SHEET

TRACK

DESCRIPTION

AEC Track System is a site-fabricated, stretched fabric system that uses the WhisperTrack® polymer track or “stretching system.” The WhisperTrack® creates a cavity for core material to be installed that can absorb, reflect, diffuse, or be a tackable surface. The track is cut in the field according to the site conditions and the panel layouts specified. The track securely grips the chosen fabric, allowing it to be stretched over the core material, creating a tailored appearance and high performance

[WATCH INSTALL VIDEO](#)

PROPERTIES

Available in ½”, 1”, and 2” track heights with other heights achievable by furring up of standard profiles. Other heights are available upon request!

Edge conditions: Bevel, radius, square, reveal, and welted

Specialty track profiles for the construction of baffles, clouds, art panels, and removable tack panels are available.

Class A fire rated - Tested as a stretched fabric panel assembly according to ASTM-E84 and ASTM-E2573 fire test standards.

***PVC Free track available upon request**

RECYCLED CONTENT

100% Post-Industrial recycled content in most track profiles.

100% Recyclable.

VOC

Low VOC rated in 1” system.

FABRIC

Finish material is selected by the client/designer. Please see our **Fabric Guidelines** sheet for information on how to select a fabric that works with our system.

[VIEW PROJECT IMAGES](#)



CORE

DESCRIPTION

Acoustitherm 600 Fiberglass Core is an engineered acoustical core designed to work within the Whisper Walls Acoustical Fabric Wall and Ceiling Systems for effective sound absorption.

PROPERTIES

Semi rigid

Recycled Content

Sound Absorptive

Moisture and fungi resistant

Excellent dimensional stability

2' x 4' Sheets for easy handling

Engineered for the Whisper Walls system

RECYCLED CONTENT

Acoustitherm 600 contains a minimum 50% post consumer recycled glass.

FIRE RATING

Tested as a stretched fabric panel assembly according to ASTM-E84 and ASTM-E2573 fire test standards.

Frequency	Noise Reduction Coefficient (NRC)
1/2" SYSTEM	0.55
1" SYSTEM	0.80
2" SYSTEM	0.95